

Essential Energy Saving Products

Lamps & Luminaires | Controls | Heating & Controls | Hand Dryers | Heat Recovery & Ventilation | Voltage Optimisation Variable Speed Drives | Renewables | EV Charging Unit Testers | Lease Finance Solutions





Contents

Lamps	
LED GLS	ò
LED Candles	ò
LED GU10	7
LED G24	7
LED 2D	7
LED Discharge	3
LED T8 Tubes8-5	
LED T5 Tubes	
LED Capsules [G4 / GY6.35 / G9]	
Luminaires	
	1
LED Battens	
LED Linear Vapour Proof Fittings	
LED Erred Vapour Froot Fittings	
Low Profile Commercial Downlights	
Backlit LED Panels	
Klip Tri-Colour LED Bulkheads14	
Tri-Colour LED Wall Packs14	
Guardian LED Floodlights15	
LED Highbays	
Solar-Powered	
Controls	1
Wall / Ceiling Mounted PIR's	
Time Lag Switches	
PIR & Microwave Sensors	
Power Factor Correction Canacitor 19	4

Heating & Controls
Designer XR Electric Radiators19
Storage Heaters
Panel Heaters
Timers & Thermostats21
Hand Dryers
Tornado ABS Automatic Hand Dryer21
Tempesta Automatic Hand Dryer22
Tempesta Plus Automatic Hand Dryer22
Heat Recovery & Ventilation
Single Room Heat Recovery Unit22
Zone 1 Whisper Quiet Fan22
Whisper Continuous All-In-One Fan22
Voltage Optimisation
Single Tap Voltage Optimisation Unit23
Multi Tap Voltage Optimisation Unit24
Variable Speed Drives
Enclosed Variable Speed Drives25
Renewables
We're All About Renewables26-27
EV Charging Unit Testers
Multifunction Installation Tester
with EV Testing Adaptor28

Lease Finance Solutions30-31



Our sustainability & social value achievements



we are the only electrical distributor to have an in-house recycling division - Waste Experts



through our partnership with McMillan Cancer Support



Independent verification of our commitment to sustainability & social value











Our sustainability & social value Strategy

Our sustainability & social value strategy is the roadmap we are using to guide our progress.

At CEF our goal is to be a leader in our sector,

and a force for good, with a focus on people, planet, and communities

Director of ESG, Sustainability, and Health & Safety





NEW

8.1W Essential LED GLS Lamps 230V

- Suitable replacement for 60W filament lamps
- Finish: Opal







Code	Сар	Lumens	1+	10+
Non-Dimm	able – War	m White – 27	700K	
2818-5049	BC / B22	810 lm	£4.25	£4.00
2818-5055	ES / E27	810 lm	£4.25	£4.00
Dimmable -	– Warm Wh	nite – 2700K		
2818-2757	BC / B22	810 lm	£5.75	£5.50
2816-1889	ES / E27	810 lm	£5.75	£5.50

Finish: Opal

2818-0558

2818-4575

2818-4725

2818-4704

2818-4701

2816-1892

2818-4713

■ Lamp life: 15,000 hrs

ENERGY SAVING COMPARISON: 8.1W LED GLS vs 60W Incandescent

4.7W Essential LED Candle Lamps

Suitable replacement for 40W filament lamps

6W LED Filament GLS Lamps 230V

- Suitable replacement for 40W filament lamps
- Finish: Clear

■ Lamp life: 15,000 hrs





Code	Сар	Lumens	1+	10+
Non-Dimma	ble – Warm	White – 2700		
2818-5088	BC / B22	806 lm	£6.25	£5.75
2818-5100	ES / E27	806 lm	£6.25	£5.75
Dimmable –	Warm Whit	e – 2700K		
2818-5097	BC / B22	806 lm	Visit ce	f.co.uk
2818-0564	ES / E27	806 lm	£7.95	£7.50

kgCO2e SAVIN	G
UP 167.67	OVER 15,000 hrs

ENERGY SAVING COMPARISON: 6W LED GLS vs 60W Incandescent

4W LED Filament Candle Lamps

- Suitable replacement for 40W filament lamps
- Finish: Clear

£4.25

£5.25

£5.25

£4.50

£5.75

£5.75

Visit cef.co.uk

Visit cef.co.uk

Visit cef.co.uk

Visit cef.co.uk

■ Lamp life: 15,000 hrs





10+	1+	Lumens	Cap	Code
	OK		ble – Warm	Non-Dimmal
f.co.uk	Visit ce	480 lm	SBC / B15	2818-4863
f.co.uk	Visit ce	480 lm	BC / B22	2818-4830
£3.75	£4.25	480 lm	SES / E14	2818-4881
f.co.uk	Visit ce	480 lm	ES / E27	2818-4845
		e – 2700K	Warm Whit	Dimmable –
£5.50	£5.95	480 lm	SBC / B15	2818-4878
£5.50	£5.95	480 lm	BC / B22	2818-4842
£5.50	£5.95	480 lm	SES / E14	2818-4896
£5.50	£5.95	480 lm	ES / E27	2818-4860

ENERGY SAVING COMPARISON: 4W LED Candle vs 40W Incandescent

kgCO2e SAVING	YOU SAVE
UP 109.61 OVER 15,000 kgC02e hrs	UP £131.63

470 lm

SBC / B15

BC / B22

SES / E14

ES / E27

BC / B22

SES / E14

ES / E27

ENERGY SAVING COMPARISON: 4.7W LED Candle vs 40W Incandescent

Suitable replacement for 60W filament

6.75W LED GLS Lamps 230V

- Finish: Opal
- Lamp life: 25,000 hrs



	Code	Cap	Lumens	1+	10+
	Non-Dimma	ble – Warn	n White – 2	700K	
	2818-4986	BC / B22	810 lm	Visit.ce	f.co.uk
	2818-4998	ES / E27	810 lm	Visit.ce	f.co.uk
	Dimmable -	- Warm Wh	ite – 2700K		
	2818-4995	BC / B22	810 lm	Visit.ce	f.co.uk
	2818-5007	ES / E27	810 lm	Visit.ce	f.co.uk
:					

	kgC02e SAVING		
UP TO	27	5.57 kgC02e	OVER 25,000 hrs

ENERGY SAVING COMPARISON: 6.75W LED GLS vs 60W Incandescent

4W LED Candle Lamps

- Suitable replacement for 40W filament lamps
- Finish: Opal
- Lamp life: 25,000 hrs



Code	Cap	Lumens	1+ 10+
Non-Dimmal	ble – Warm V	White – 270	OK
2818-4539	SBC / B15	480 lm	Visit cef.co.uk
2818-4521	BC / B22	480 lm	Visit cef.co.uk
2818-4551	SES / E14	480 lm	Visit cef.co.uk
2818-4527	ES / E27	480 lm	Visit cef.co.uk
Dimmable –	Warm White	e – 2700K	
2818-4548	SBC / B15	480 lm	Visit cef.co.uk
2818-2754	BC / B22	480 lm	Visit cef.co.uk
2818-4560	SES / E14	480 lm	Visit cef.co.uk
2818-4536	ES / E27	480 lm	Visit cef.co.uk

ĺ	kgCO2e SAVING
	UP 186.30 OVER 25,000 kgC02e hrs

ENERGY SAVING COMPARISON: 4W LED Candle vs 40W Incandescent





NEW

3.7W Essential LED GU10 Lamps 230V - Pack of 10

- Suitable replacement for 35 and 50W halogen lamps
- Beam angle: 38°
- Lamp life: 20,000 hrs







Code	Lumens	Colour Temp	Equivalent Price Each	1+
Non-Dimmabl				
2818-4602	352 lm	Warm White – 3000K	£1.68	£16.75
2818-4515	352 lm	Cool White - 4000K	£1.68	£16.75
2818-4590	352 lm	Daylight – 6000K	£1.68	Visit cef.co.uk
Dimmable				
2818-4512	257 lm	Warm White – 3000K	£2.28	Visit cef.co.uk
2818-4509	257 lm	Cool White – 4000K	£2.28	Visit cef.co.uk
2818-4602	352 lm	Daylight – 6000K	£2.28	Visit cef.co.uk

WP 186.30 OVER 20,000 To 186.30 hrs

VOU SAVE
UP **£223.74** OVER 20,000 hrs

ENERGY SAVING COMPARISON: 5W LED GU10 vs 50W Halogen

8W G24 LED Lamps

- Suitable replacement for 18 and 26W compact fluorescent lamps
- Rotating end cap



Code	Сар	Length	Lumens	1+	10+
Non-Dimma	ble – Cool White – 40	OOK			
2275-5286	G24 2 Pin	145 mm	800 lm	£16.95	£16.50
2275-5325	G24 4 Pin	145 mm	800 lm	£16.95	£16.50

kgC02e SAVING
UP 124.20 OVER 25,000 To 124.8602e hrs

VOU SAVE
UP **£149.16** OVER 25,000 hrs

ENERGY SAVING COMPARISON: 8W LED Compact vs 26W Compact & Control Gear (6W)

5W LED GU10 Lamps

- Suitable replacement for 50W halogen lamps
- Beam angle: 60°
- Lamp life: 25,000 hrs



3 YEARS GUARANTEE

FROM £4.10 £+VAT

Code	Lumens	Colour Temp	1+	10+
Non-Dimma	ible			
2253-2821	500 lm	Warm White – 3000K	£4.10	£3.85
2253-2815	510 lm	Cool White – 4000K	£4.10	£3.85
Dimmable				
2253-2824	500 lm	Warm White – 3000K	£6.10	£5.85
2253-2818	510 lm	Cool White – 4000K	£6.10	£5.85

۱		kgCUZE SAVINE	
	UP TO	232.88 kgC02e	OVER 25,000 hrs

	YOU SAVE	
UP TO	£279.68	OVER 25,000 hrs

ENERGY SAVING COMPARISON: 5W LED GU10 vs 50W Halogen

LED 2D Lamps

- Suitable replacement for 16, 28 and 38W compact fluorescent 2D lamps
- Lamp life: 30,000 hrs



3 YEARS GUARANTEE

ONLY £19.75 £VAT

Code	Wattage	Cap	Lumens	1+	10+		
Non-Dimmal	Non-Dimmable – Cool White – 4000K						
2123-0989	8W	GR8 2 Pin	800 lm	£19.75	£18.75		
2123-0992	8W	GR10q 4 Pin	800 lm	£19.75	£18.75		
2123-0980	14W	GR8 2 Pin	1400 lm	£21.95	£20.95		
2123-0983	14W	GR10q 4 Pin	1400 lm	£21.95	£20.95		
2123-0986	18W	GR10q 4 Pin	2000 lm	£26.95	£25.95		

kgC02e SAVING
UP186.30 OVER
T0 186.30 SOVER
kgC02e hrs

VOU SAVE
UP **£223.74** OVER 30,000 hrs

ENERGY SAVING COMPARISON: 18W LED 2D vs 38W 2D & Control Gear (10W)

LED Retrofit Discharge Lamps

- Suitable replacement for HID lamps
- Beam angle: 300°
- Lamp life: 25,000 hrs







Code	Wattage	Сар	Length	Ø	Lumens	Replacement For	1+
Non-Dimmabl	le – Daylight – 6000K –	Suitable for Bollards,	Bulkheads and La	anterns			
1414-1569	11W	ES / E27	165 mm	65 mm	1150 lm	70W HID	£45.75
2253-2830	15W	ES / E27	165 mm	65 mm	1575 lm	70W HID	£49.95
Non-Dimmabl	e – Daylight – 6000K –	Suitable for Lowbays,	, Highbays, Floodl	ights and Lanterr			
2448-1897	20W	ES / E27	178 mm	93 mm	2600 lm	70W HID	£48.95
2448-1903	30W	ES / E27	188 mm	93 mm	3900 lm	70 - 150W HID	£60.85
2448-1900	30W	GES / E40	208 mm	93 mm	3900 lm	70 - 150W HID	£60.85
2448-1906	60W	GES / E40	280 mm	93 mm	8000 lm	250W HID	£73.75
2448-1909	85W	GES / E40	285 mm	106 mm	11000 lm	250 - 400W HID	£88.50
2448-1891	100W	GES / E40	288 mm	120 mm	13000 lm	250 - 400W HID	£98.50
2448-1894	120W	GES / E40	308 mm	120 mm	15000 lm	400W HID	£114.95

3 YEARS GUARANTEE

kgC02e SAVING

OVER 25,000 hrs

ENERGY SAVING COMPARISON: 85W LED HID vs 400W HID & Control Gear [45W]

LED T8 Tri-Colour Glass Tubes

- Suitable replacement for fluorescent tubes
- Selectable colour temperature: Warm white 3000K, cool white 4000K and daylight 6500K
- Complete with LED starter for use in switch start retrofit installations
- Beam angle: 300°
- Lamp life: 25,000 hrs



Code	Length	Wattage	Lumens	1+	5+		
Non-Dimma	Non-Dimmable						
2772-8017	2 ft	9W	945 lm / 990 lm / 990 lm	£9.25	£8.80		
2772-8020	3 ft	14W	1540 lm / 1680 lm / 1680 lm	£11.25	£10.80		
2772-8023	4 ft	18W	1980 lm / 2160 lm / 2160 lm	£14.25	£13.75		
2772-8026	5 ft	24W	2640 lm / 2880 lm / 2880 lm	£16.95	£16.50		
2772-8029	6 ft	30W	3300 lm / 3600 lm / 3600 lm	£32.75	£31.75		

OVER

OVER 25,000

ENERGY SAVING COMPARISON: 24W LED T8 CCT Tube vs 58W T8 & Control Gear (8W)

LED T8 Polycarbonate Tube

Suitable replacement for fluorescent tubes







LED T8 Glass Tubes



■ Beam angle: 300°

■ Lamp life: 25,000 hrs



Code	Length	Wattage	Lumens	1+	5+	
Non-Dimmable – Cool White – 4000K						
2096-0905	2 ft	9W	900 lm	£7.95	£7.45	
2096-0911	3 ft	14W	1500 lm	£10.25	£9.80	
2096-0923	4 ft	18W	1950 lm	£13.15	£12.65	
2096-0932	5 ft	24W	2600 lm	£15.75	£15.25	
2096-0938	6 ft	30W	3400 lm	£25.95	£24.95	

25,000 hrs TO

ENERGY SAVING COMPARISON: 30W LED T8 Tube vs 70W T8 & Control Gear (8W)

LED T5 Glass Tubes

- Suitable replacement for fluorescent tubes
- Beam angle: 200°
- Lamp life: 25,000 hrs





Code	Length	Wattage	Lumens	1+	10+
Non-Dimmal	ole – Cool White –	4000K			
2772-8041	2 ft	8W	880 lm	£11.05	£10.75
2772-8032	3 ft	12W	1320 lm	£13.75	£13.25
2772-8035	4 ft	16W	1760 lm	£15.50	£14.95
2772-8038	5 ft	20W	2200 lm	£17.75	£17.25

kgC02e SAVING

OVER UP 25,000 hrs TO

ENERGY SAVING COMPARISON: 20W LED T5 Tube vs 35W T5 & Control Gear (5W)

2W LED G4 Capsule Lamps

- Pack of 2

- Suitable replacement for 10 and 20W halogen lamps
- Lamp life: 15,000 hrs



Code	Lumens	1+	10+		
Non-Dimma	able – Warm White – 3				
2196-2761	200 lm	£10.50	£9.95		
Non-Dimmable – Cool White – 4000K					
2247-2401	200 lm	£10.50	£9.95		

OVER T0

ENERGY SAVING COMPARISON: 2W LED G4 vs 20W Halogen G4

3.3W LED G9 Capsule Lamps

- Pack of 2

- Suitable replacement for 40W halogen lamps
- Lamp life: 15,000 hrs



Code	Lumens	1+	10+		
Non-Dimma	ble – Warm White – 30				
2196-2764	350 lm	£10.95	£10.50		
Non-Dimmable – Cool White – 4000K					
2247-2404	350 lm	£10.95	£10.50		

OVER T0

ENERGY SAVING COMPARISON: 3.3W LED G9 Vs 40w Halogen G9

LED GY6.35 Capsule Lamps 12V

- Suitable replacement for 35 and 50W halogen lamps
- Lamp life: 15,000 hrs



1 YEAR

Code	Wattage	Lumens	1+	10+
Non-Dimma	able – Warn	n White – 270		
2786-2006	2.6W	300 lm	£7.50	£6.95
2786-2012	4W	470 lm	£8.25	£7.75
Non-Dimma	able – Cool	White – 4000		
2786-2003	2.6W	300 lm	£7.50	£6.95
2786-2009	4W	470 lm	£8.25	£7.75

ĺ	kgCO2e SAVING					
	UP 142.83 OVER 15,000 hrs					

OVER TO

ENERGY SAVING COMPARISON: 4W LED G4 vs 50W Halogen GY6.35





LED Non-Corrosive Fittings IP65

- Polycarbonate body and purpose-designed opal diffuser
- Integrated LED
- Colour temperature: Cool white 4000K
- Lamp life: 50,000 hrs
- Impact rating: IK08
- Mounted: Surface or suspended

Microwave features:

- Detection angle [ceiling]: 360° [wall]: 150°
- Detection range: 10 m
- Timer adjustment: 5 secs, 30 secs, 90 secs, 5 mins, 20 mins or 30 mins



Includes:

- Stainless steel fixing clips
- Gear tray extension cords

Code	Size	Wattage	Lumens	Length	Width	Depth		Pri	ce	
Standard										
2613-7831	2 ft	9W	1100 lm	600 mm	96 mm	79 mm	1+	£30.25	10+	£28.75
2613-7834	2 ft	18W	2200lm	600 mm	96 mm	79 mm	1+	£34.75	10+	£33.25
2613-7894	4 ft	18W	2200lm	1200 mm	96 mm	79 mm	1+	£31.95	10+	£30.50
2613-7840	4 ft	40W	4800 lm	1200 mm	96 mm	79 mm	1+	£43.75	10+	£42.25
2613-7846	5 ft	23W	2800lm	1500 mm	96 mm	79 mm	1+	£36.50	10+	£34.95
2613-7852	5 ft	48W	5800 lm	1500 mm	96 mm	79 mm	1+	£50.75	10+	£49.25
2613-7858	6 ft	27W	3200lm	1800 mm	96 mm	83 mm	1+	£51.50	10+	£49.95
2613-7864	6 ft	55W	6600 lm	1800 mm	96 mm	83 mm	1+	£61.95	10+	£60.50
Standard -	Micro	wave Sen	sor							
2726-9278	5 ft	23W	2800lm	1500 mm	96 mm	79 mm	1+	£52.95	10+	£51.50
2726-9272	5 ft	48W	5800 lm	1500 mm	96 mm	79 mm	1+	£66.25	10+	£64.50
3 hr Mainta	ained l	Emergency	у							
2613-7837	4 ft	18W	2200 lm	1200 mm	96 mm	79 mm	1+	£80.95	3+	£78.95
2613-7843	4 ft	40W	4800 lm	1200 mm	96 mm	79 mm	1+	£91.25	3+	£89.25
2613-7849	5 ft	23W	2800lm	1500 mm	96 mm	79 mm	1+	£85.75	3+	£83.75
2613-7855	5 ft	48W	5800 lm	1500 mm	96 mm	79 mm	1+	£103.95	3+	£101.95
2613-7861	6 ft	27W	3200lm	1800 mm	96 mm	83 mm	1+	£99.95	3+	£97.95
2613-7867	6 ft	55W	6600 lm	1800 mm	96 mm	83 mm	1+	£112.95	3+	£110.50
3 hr Mainta	ained l	Emergency	y – Microv	wave Senso	or					
2726-9281	5 ft	23W	2800lm	1500 mm	96 mm	79 mm	1+	£116.95	3+	£112.95
2726-9275	5 ft	48W	5800 lm	1500 mm	96 mm	79 mm	1+	£140.95	3+	£136.95



kgC02e SAVING

50,000 kgCO2e hrs

YOU SAVE

OVER 50,000

ENERGY SAVING COMPARISON:

48W LED Non Corrosive vs 2 x 58W T8 Fluorescent Lamps & Control Gear [26W]





video demonstration







LED Linear Vapour Proof Fittings IP65

- Slim extruded single-piece polycarbonate body and opal diffuser
- Colour temperature: Cool white 4000K
- Lamp life: 25,000 hrs
- Dimensions: 53 mm[W] x 35 mm[D]
- Mounted: Surface or suspended











Includes:

- Stainless steel fixing clips
- Entry gland
- Quick-fit terminals

FROM	
9 1.7	5
£ Z4 +vA	Ī

Code	Size	Wattage	Lumens	Length	1+	10+
Single						
2607-5575	4 ft	36W	3600 lm	1261 mm	£24.75	£23.75
2607-5578	5 ft	45W	4500 lm	1541 mm	£29.25	£28.25
2607-5581	6 ft	60W	6000 lm	1841 mm	£44.25	£43.25

kgCO2e SAVING						
UP TO	93.15 kgC02e	OVER 25,000 hrs				

YOU SAVE							
UP TO	£111.87	OVER 25,000 hrs					

ENERGY SAVING COMPARISON: 60W LED Vapour Proof Vs 70w T8 Fluorescent Lamp & Control Gear (8W)

5.5W LED Fire Rated Tri-Colour Downlight IP65

- Range: LED FRD
- Fixed LED downlight
- Selectable colour temperature: Warm white 3000K, cool white 4000K & daylight 6000K
- Colour selectable via switch located underneath the bezel
- Lumen output: 450 lm / 500 lm / 500 lm
- Integral driver and separate prewired loop in / out plug-and-play connector
- Dimmable
- Fire rated: 30, 60 and 90 mins
- Lamp life: 25,000 hrs





Code	Finish	Beam Angle	Depth	Ø	Cut Out Ø	1+	10+
Bezel Includ	ed						
2743-9417	White	60°	56 mm	87 mm	70 - 75 mm	£17.50	£16.95

kgCO2e SAVING					
UP TO	230.29 kgC02e	OVER 25,000 hrs			



ENERGY SAVING COMPARISON: 5.5W LED Downlight vs 50W Halogen

4.5W / 5.5W / 7.5W LED Fire Rated Tri-Colour Downlight IP65

- Range: LED FRD
- Fixed LED downlight
- Selectable colour temperature: Warm white 3000K, cool white 4000K and daylight 6500K
- Colour selectable via switch located underneath the bezel
- Wattage selectable via switch located on the integral driver
- Lumen output [4.5W]: 400 lm / 430 lm / 400 lm [5.5W]: 500 lm / 550 lm / 500 lm [7.5W]: 600 lm / 700 lm / 600 lm
- Integral driver and separate prewired loop in / out plug-and-play connector
- Dimmable
- Fire rated: 30, 60 and 90 mins

Finish

■ Lamp life: 30,000 hrs

2743-9414 White 60°





WATTAGE SELECTOR



		·	
		YOU SAVE	
VER 0,000 rs	UP TO	£331.88	OVER 30,000 hrs

56 mm 86 mm 70 - 75 mm **£20.50 £19.95**

ENERGY SAVING COMPARISON: 5.5W LED Downlight vs 50W Halogen









Also available...

Metal bezels for use with Fusion downlights - [2743-9417 and 2743-9414 only]

Code	Finish	1+	10+
2743-9093	Anthracite	£3.15	£2.95
2743-9096	Black	£3.15	£2.95
2743-9099	Chrome	£3.15	£2.95
2743-9102	Polished Brass	£3.15	£2.95
2743-9105	Satin Nickel	£3.15	£2.95
2743-9108	White	£3.15	£2.95













LED Low Profile Commercial Downlights IP20

- Low profile recessed downlight with opal polycarbonate diffuser
- Ideal replacement for existing CFL fixtures
- Mounted: Recessed
- Lamp life: 25,000 hrs



2 YEARS Guarantee

FROM £ 10.85

Includes:


■ Plug-and-play driver

Code	Wattage	Lumens	Depth	Ø	Cut Out Ø	1+	10+
Cool White -	4000K						
2634-4567	6W	450 lm	21 mm	128 mm	115 mm	£10.85	£10.30
2634-4558	12W	900 lm	21 mm	170 mm	150 mm	£14.60	£14.10
2634-4561	18W	1600 lm	21 mm	229 mm	210 mm	£17.40	£16.70
2634-4564	24W	1900 lm	21 mm	298 mm	280 mm	£27.75	£27.50

UP 238-05 OVER 25,000 hrs

UP **£285.89** OVER 25,000 hrs

ENERGY SAVING COMPARISON: 18W LED Downlight vs 2 x 26W Compact & Control Gear [12W]



36W Backlit TP[a] LED Panels IP20

- Aluminium body with low glare opal polycarbonate TP[a] diffuser
- Mounted: Recessed
- Lamp life: 50,000 hrs



1 YEAR ON-SITE GUARANTEE

5 YEARS GUARANTEE

FROM £**26**.95

Includes:


■ Plug-and-play driver

Code	Lumens	Length	Width	Depth	1+	10+			
Non-Dimmable – Warm White – 3000K									
2676-5536	3820 lm	595 mm	595 mm	34 mm	£26.95	£25.95			
Non-Dimmab	le – Cool Whit	e – 4000K							
2676-5530	3820 lm	595 mm	595 mm	34 mm	£26.95	£25.95			
Non-Dimmable – Daylight – 6500K									
2676-5533	3820 lm	595 mm	595 mm	34 mm	£26.95	£25.95			

WP 538.20 OVER 50,000 hrs

UP **£646.36** OVER 50,000 hrs

ENERGY SAVING COMPARISON: 36W LED Panel Vs 4x18W Fluorescent Lamps & Control Gear (16W)



Luminaires

12W / 16W Klip LED Tri-Colour Bulkheads IP65

- LED Bulkhead with opal diffuser
- Selectable colour temperature: Warm white 3000K, cool white 4000K or daylight 6500K
- Switch located on the driver takes the fitting down to 12W for increased energy savings
- Lumen output [12W]: 1,200 1,300 lm [16W]: 1,600 - 1,700 lm
- Lamp life: 30,000 hrs

Microwave features:

- Detection angle: 360°
- Detection range: 12 m
- Timer adjustment: 0 20 mins

Sensor

Microwave

Microwave

No







Includes:

2704-3168

2704-3174

2704-3171

2704-3177

■ Standard white bezel



£29.30

£47.75

£49.95

£67.95

£30.75 5+

£49.75 5+

£51.95 3+

£69.95 3+





30,000

ENERGY SAVING COMPARISON: 16W LED Bulkhead vs 28W 2D & Control Gear (6W)

20W Tri-Colour LED Wall Packs IP65

Depth

95 mm

95 mm

95 mm

95 mm

340 mm

340 mm

340 mm

340 mm

1+

1+

1+

- Die-cast aluminium body and polycarbonate diffuser
- Push-fit connectors for easy installation
- Selectable colour temperature: Warm white 3000K, cool white 4000K or daylight 6500K
- Lumen output: 1,500, 1,600 or 1,550 lm
- Lamp life: 50,000 hrs







Code	Sensor	Height	Width	Depth	1+	3+
2641-1884	No	221 mm	207 mm	82 mm	£79.95	£77.95
2641-1887	Photocell	221 mm	207 mm	82 mm	£89.25	£87.25















Guardian LED Floodlights IP65

- Die-cast aluminium powder-coated body
- Integrated LED
- Colour temperature: Cool white 4000K
- Lamp life: 50,000 hrs

PIR Features:

- Detection angle: 120°
- Detection range: Up to 10 m
- Timer adjustment: 10 secs 7 mins

Adjustable bracket

■ 1 m Cable



video demonstration

Code	Wattage	Lumens	Height	Width	Depth	1+	3+
Standard							
2672-6707	15W	1950 lm	188 mm	129 mm	34 mm	£24.50	£23.50
2672-6719	30W	3900 lm	238 mm	173 mm	42 mm	£37.75	£36.75
2672-6728	50W	6500 lm	250 mm	188 mm	42 mm	£56.50	£54.95
2672-6734	80W	10400 lm	302 mm	250 mm	52 mm	£111.50	£108.50
2672-6704	100W	13000 lm	358 mm	279 mm	57 mm	£126.95	£123.95
2672-6710	150W	19500 lm	405 mm	329 mm	62 mm	£156.50	£153.50
2672-6716	250W	32500 lm	471 mm	401 mm	62 mm	£241.95	£238.95
PIR							
2672-6713	15W	1950 lm	250 mm	129 mm	51 mm	£33.75	£32.75
2672-6722	30W	3900 lm	303 mm	173 mm	53 mm	£44.75	£42.75
2672-6731	50W	6500 lm	315 mm	188 mm	54 mm	£68.25	£66.25





FROM

kgCO2e SAVING

Luminaires

FUSI: N

OVER

ENERGY SAVING COMPARISON: 50W LED Floodlight vs 500W

Tungsten Halogen Lamp

LED Highbay Fittings IP65

- Ideal for replacement of SON or metal halide highbays
- Die-cast aluminium housing with integral driver and polycarbonate lens
- 1 10V Dimming as standard
- Beam angle: 120°
- Colour temperature: Cool white 4000K
- Lamp life: 50,000 hrs

Includes:

■ 1 m Cable

* WHILE STOCKS LAST

Code	Wattage	Lumens	Depth	Ø	1+	10+
2681-1316*	100W	14000 lm	159 mm	280 mm	£102.50	£100.50
2681-1319*	150W	21000 lm	159 mm	280 mm	£112.95	£110.95
2681-1322*	200W	28000 lm	169 mm	330 mm	£159.95	£157.95
2681-1325*	240W	33600 lm	169 mm	330 mm	£169.95	£167.95
Code	Suitable For		Beam Angle		1+	10+
Aluminium R	eflector					
2681-1352*	100W and 15	OW	90°		£24.75	£23.75
2681-1337*	200W and 24	40W	90°		£33.75	£32.75
Polycarbona	te Lens					
2681-1346*	100W and 15	OW	90°		£13.75	£13.25
2681-1331*	200W and 24	40W	90°		£14.25	£13.75
Polycarbona	te Reflector					
2681-1349*	100W and 15	OW	-		£44.95	£43.95
2681-1334*	200W and 24	40W	-		£46.50	£45.50
Mounting Bra	acket					
2681-1343*	100W and 15	OW	-		£12.75	£12.25
2681-1328*	200W and 24	40W	-		£17.50	£16.95
Code	Description				1+	3+
2681-1340*	Microwave S	ensor			£29.95	£28.50
2604-1012	Remote Con	trol for Micro	wave Sensor		£29.95	£28.50















OVER 50,000

66.85 OVER 50,000

ENERGY SAVING COMPARISON:

150W LED Highbay vs 400W Discharge Lamp & Control Gear [45W]



6W Solar-Powered LED Security Twinspot with PIR IP44

- Energy-saving, solar-powered security twinspot
- Colour temperature: Daylight 6500K
- Lumen output: 600 lm
- Lamp life: 30,000 hrs

PIR Features:

- Detection angle: 130°
- Detection range: 8 m
- Timer adjustment: 10 secs 1 min

Includes:

■ Solar panel with 5 m lead

1 YEAR GUARANTEE £



Code	Height	Width	Depth	1+	3+
2092-6510	189 mm	334 mm	120 mm	£48.25	£46.75

Wall / Ceiling Mounted PIRs IP44

- Auto override
- Detection angle: 180°
- Detection range: 12 m
- Timer adjustment: 10 secs - 10 mins

Load rating:

Max. 1,000W [4A] Incandescent lamps



1 YEAR GUARANTEE



Code	Colour	Height	Width	Projection	1+	3+
1249-4044	Black	80 mm	70 mm	125 mm	£19.25	£18.50
1249-4047	White	80 mm	70 mm	125 mm	£19.25	£18.50

Wall Mounted PIRs IP44

- Adjustable sensitivity, time and lux
- Lux adjustment: 3 2,000 lx
- Detection angle: 180°
- Detection range: 12 m
- Timer adjustment: 10 secs - 15 mins
- Mounted: Wall





Load rating:

- Max. 1,200W [5A] Incandescent lamps
- Max. 300W [1.2A] LED Lamps [up to six lamps]

1 YEAR GUARANTEE



Code	Colour	Height	Width	Projection	1+	3+
2543-0164	Black	120 mm	78 mm	52 mm	£11.50	£10.75
2543-0167	White	120 mm	78 mm	52 mm	£11.50	£10.75

6W Solar-Powered LED Floodlight with PIR IP44

- Energy-saving, solar-powered floodlight
- Polycarbonate body
- Colour temperature: Daylight 6000K
- Lumen output: 480 lm
- Lamp life: 30,000 hrs

PIR Features:

- Detection angle: 130°
- Detection range: 8 m
- Timer adjustment: 10 secs 1 min

Includes:

■ Solar panel with 5 m lead



GUARANTEE
1+

Code	Height	Width	Depth	1+
2261-4100	203 mm	210 mm	219 mm	Visit cef.co.uk

Wall / Ceiling Mounted PIRs IP55

- Adjustable detector head and lux
- Supplied with lens shield
- Detection angle: 45 360°
- Detection range: 16 m
- Timer adjustment:
- 5 secs 15 mins
- Mounted: Wall, ceiling or corner



Load rating:

- Max. 2,200W [9A] Incandescent lamps
- Max. 200W [0.8A] LED Lamps

Code	Colour	Height	Width	Projection	1+	3+
2613-8074	Black	147 mm	88 mm	50 mm	£32.25	£30.75
2613-8071	White	147 mm	88 mm	50 mm	£32.25	£30.75

Wall / Ceiling Mounted PIRs IP55

- Adjustable sensitivity, time and lux
- Supplied with lens shield
- Detection angle: 240°
- Detection range: 4 12 m
- Timer adjustment: 1 20 mins
- Mounted: Wall, ceiling or corner



Load rating:

- Max. 2,000W [8A] Incandescent lamps
- Max. 400W [1.6A] LED Lamps



ONLY £**35**.50

Code	Height	Width	Projection	1+	3+
2613-8179	74 mm	72 mm	133.6 mm	£35.50	£33.95



Wall / Ceiling Mounted PIRs IP65

- Remote control included to adjust lux, range and timer
- Lux adjustment: 3 2,000 lx
- Detection angle: 180°
- Detection range: 12 m
- Timer adjustment: 3 secs 30 mins



Load rating:

- Max. 1,200W [5A] Incandescent lamps
- Max. 300W [1.2A] LED Lamps

Code	Colour	Height	Width	Projection	1+	3+
2364-1459	Black	52 mm	80 mm	120 mm	£20.05	£19.25
2364-1456	White	52 mm	80 mm	120 mm	£20.05	£19.25

Long Distance Wall / Ceiling Mounted PIRs IP54

- Adjustable sensitivity, time and lux
- Lux adjustment: 10 2,000 lx
- Detection angle: 270°
- Detection range: 18 m

Load rating:

■ Timer adjustment: 5 secs - 4 mins

Max. 2,000W [8A] Incandescent lamps





■ Max. 250W [1	A] LED Lam	ıps [up to six	lamps]	GUARAN	TEE E	U+VAT
Code	Colour	Height	Width	Projection	1+	3+
2543-0146	Black	86 mm	96 mm	137 mm	£48.50	£46.95
2543-0149	White	86 mm	96 mm	137 mm	£48.50	£46.95



Columbus® Pneumatic Time Lag Switch

- No neutral required
- Timer adjustment: 5 secs 5 mins
- BS EN 60669-2-3:2006



Load rating:

- 1,440W [6A] Incandescent lamps and resistive loads
- 720W [3A] LED Lamps







Code	Configuration	No. of Wire Connections	1+	3+
0003-7666	Single Contact	3	£26.75	£25.75

16A Pushbutton Time Lag Switches

- Master switch can be interlinked with any Elkay slave switches [only one master per circuit1
- Suitable for incandescent and fluorescent lamps and resistive loads
- Illuminated blue locator ring
- One minute countdown LED indicator
- Requires capacitor [1865-9914] for all types of low wattage loads including LED lighting [sold separately – page 19]
- Concealed fixing screws
- Timer adjustment: 2 mins 2 hrs
- BS EN 60669-2-3



WIRE	3 WIRE
YEARS	6 YEARS
UARANTEE	GUARANTE



Code	Configuration	No. of Wire Connections	1+	3+
0704-0065	Master	2	£47.95	£46.95
0704-0113	Master	3	£47.50	£46.50

16A Pushbutton Time Lag Switch

- Compatible with any two or three wire master switches
- Illuminated blue locator ring requires three wire connections to masters switch
- Time cancellation function
- Timer adjustment: 2 mins 2 hrs





Code	Configuration	No. of Wire Connections	1+	3+
0704-0071	Slave	2	£27.50	£26.50



Controls

16A Two Wire PIRs

- No neutral required
- Please note: Capacitor [1865-9914] will often be required when switching certain types of loads
- Detection angle: 360°
- Detection range: 5 7 m
- Timer adjustment: 2 mins 2 hrs
- BS EN 60669-2-3:2006



Code	Description	Height	Width	Depth	1+	3+
0704-0101	Two Wire	85 mm	85 mm	8 mm	£76.95	£74.95
0704-0107	Slave	85 mm	85 mm	8 mm	£37.95	£36.95

16A Three Wire PIR IP66

- Please note: Capacitor [1865-9914] will often be required when switching certain types of loads
- Detection angle: 360°
- Detection range: 5 7 m
- Includes backbox with M20 knockouts
- Timer adjustment: 2 mins 2 hrs



Code	Height	Width	Depth	1+
0704-0161	85 mm	85 mm	65 mm	Visit cef.co.uk

16A Microwave Sensor

- Suitable for all lighting types
- Switch with lux level sensing
- Please note: Capacitor [1865-9914] will often be required when switching certain types of loads
- Mounting height: 1.2 2.5 m
- Detection range: 30 m
- Timer adjustment: 2 mins 2 hrs
- Clip-on front cover conceals screws

Mounted: Standard 35 mm backboxBS EN 60669-2-1:2004+A12:2010	6 YEARS GUARANTI	e E	3.5U 3.4VAT
Code		1+	3+
1019-6221		£63.50	£61.50

16A Weatherproof Pushbutton Time Lag Switch IP66

- Master switch can be interlinked with any Elkay secondary switches [only one master per circuit]
- Commonly used for outdoor patio or infrared heaters and where there is a neutral to control all load types of lighting
- Illuminated blue locator ring
- One minute countdown LED indicator
- Includes backbox with M20 knockouts
- Timer adjustment: 2 mins 2 hrs





Code	No. of Wire Connections	1+	3+
0704-0125	3	£56.75	£55.25

Time Lag Switch

- Saves cost and energy by automatically switching off the light after a preset period of time
- Replaces existing lighting control
- Timer must be set before installation
- No neutral required
- Requires 25 mm backbox
- BS FN 60669









Code	Timer Adjustment	Current Rating	No. of Wire Connections	1+
Electronic				
1865-9911	20 secs - 25 mins	5A Incandescent - 5A Fluorescent	2	Visit cef.co.uk

10A Time Lag Switches

- Suitable for resistive loads and incandescent, fluorescent, CFL and LED lamps
- Requires 25 mm backbox
- Capacitor will often be required when switching certain types of loads - sold separately [1865-9914]
- Timer adjustment: 2 60 mins
- BS EN 60669

PIR Features:

Detection angle: 100°

ONLY

■ Detection range: 7 m







D		L)	
Г	I	I	١	

Code	Туре	No. of Wire Connections	1+	3+
1865-9896	PIR	2	£84.95	£82.95
1865-9899	Pushbutton	3	£47.50	£45.50
1865-9905	PIR	3	£70.50	£68.50









6A Three Wire Ceiling PIR

- Neutral required
- Multiple PIRs can be interlinked to cover large areas
- Please note: Capacitor [1865-9914] will often be required when switching certain types of loads
- Mounting height: 2.4 m
- Detection angle: 360°
- Detection range: 7 m
- Timer adjustment: 30 secs 30 mins





Code	Depth	Ø	Cut Out Ø	1+	3+
2639-5630	70 mm	77 mm	64 mm	£17.50	£15.95

10A Ceiling PIR

- Neutral required
- Please note: Capacitor will often be required when switching certain types of loads – sold separately [1865-9914]
- Lux and sensitivity adjustment
- Mounting height: 2.4 m
- Detection angle: 360°
- Detection range: 7 m
- Timer adjustment: 10 secs 1 hr
- BS EN 60669

Includes:

- White and chrome interchangeable bezels
- Surface mounting hackhox

YEARS



Code	Depth	Ø	Cut Out Ø	1+	3+
2816-2918	72 mm	77 mm	64 mm	£47.25	£46.25

Power Factor Correction Capacitor

- Designed to assist with the switching of electronic timers when using low wattage lighting
- Suitable for use with 2D fittings, energysaving lamps, LEDs or any low power consuming load
- Can also be used with contactors to assist in the switching of loads above 16A when using
- Ideal for use with wire switches

intolling of toddo above		
g electronic timers	-	
ith two and three		

Suitable for all AC voltages below.	/ nn

- 4 Microfarad capacitance [4μf]
- EN 60252





Code 1865-9914 Visit cef.co.uk



Designer XR Electric Radiators

Stylish, electronic radiators featuring a built-in, state-of-the-art, energy management and control system based on an integrated range of technical features.

- Built-in digital programmer with seven heating schedules, plus one bespoke option
- 150W Per fin for faster heat up time
- High-precision chrono thermostat controls temperature to within ± 0.2°C
- Open window technology
- Adaptive start: Anticipatory control

Includes:

- Wall bracket
- 1.5 m Cable

- Three temperature settings: Comfort, economy and anti-freeze
- Tamper-proof lock-off facility
- Thermal safety limiter: 75°C Maximum surface temperature
- Mounted: Wall
- IP24
- Complies with Lot 20
- IEC 62233:2005

Code	Power Rating	Height	Width	Depth	1+	3+
2728-2193	500W	590 mm	345 mm	100 mm	£235.95	£230.95
2728-2196	750W	590 mm	525 mm	100 mm	£281.95	£276.95
2728-2181	1 kW	590 mm	605 mm	100 mm	£322.95	£317.95
2728-2184	1.2 kW	590 mm	765 mm	100 mm	£372.50	£367.50
2728-2187	1.5 kW	590 mm	845 mm	100 mm	£424.95	£419.95
2728-2190	1.8 kW	590 mm	1005 mm	100 mm	£465.95	£460.95



GUARANTEE

Heating

Storage Heaters

- Controllable electronic heat to match user lifestyle
- High-density cells dynamically store energy, using less space than other storage heaters
- Seven day electronic timer with electronic thermostat
- Dynamic efficiency+ technology accurate to ± 0.2°C
- Uses off-peak and peak tariffs [requires two supplies]
- Open window technology
- Free 3D AutoCAD heating design scheme service [details on page 1187 CEF Catalogue Issue 17]
- Mounted: Floor [secured to wall]
- IPX4
- Complies with Lot 20

Includes:

- Wall bracket
- Support feet
- High-density bonded magnetite energy cell packs

BEAB

Approved

Code	Power Rating	Height	Width	Depth	1+	3+
2297-0182	500W	749 mm	581 mm	182 mm	£551.95	£541.95
2297-0317	750W	749 mm	703 mm	182 mm	£601.95	£591.95
2297-0320	1 kW	749 mm	825 mm	182 mm	£668.95	£658.95
2297-0323	1.25 kW	749 mm	947 mm	182 mm	£744.95	£734.95
2297-0326	1.5 kW	749 mm	1069 mm	182 mm	£811.95	£801.95



2 YEARS **ON-SITE** GUARANTEE

IO YEARS CONSTRUCTION

HEATSTORE THE TOTAL ELECTRIC HEATING SOLUTION

Panel Heaters

- Slim and contemporary design suitable for domestic and commercial use
- Requires wall mounted wireless controller [sold separately – see page 21]
- Mounted: Wall
- IP24

■ Complies with Lot 20



Code	Power Rating	Height	Width	Depth	1+	3+
2379-6436	500W	430 mm	442 mm	93 mm	£143.95	£141.95
2379-6439	750W	430 mm	442 mm	93 mm	£146.50	£144.50
2379-6427	1 kW	430 mm	614 mm	93 mm	£159.95	£157.95
2379-6430	1.5 kW	430 mm	720 mm	93 mm	£174.95	£172.95
2379-6433	2 kW	430 mm	852 mm	93 mm	£182.95	£180.95

High Heat Retention Storage Heaters

- Seven day programming with four time / temperature settings per day
- High-density cells dynamically store energy, using less space than other storage heaters
- Digital thermostat for accurate heating control ± 0.2°C
- Open window technology
- Adaptive start: Anticipatory control
- Free 3D AutoCAD heating design scheme service [details on page 1187] CEF Catalogue Issue 17]
- Mounted: Floor [secured to wall]
- IPX4
- SAP Approved
- Complies with Lot 20

Includes:


- Wall bracket
- Support feet
- High-density bonded magnetite energy cell packs



10 YEARS GUARANTEE

Code	Power Rating	Height	Width	Depth	1+	3+
2609-5093	500W	730 mm	580 mm	185 mm	£642.95	£632.95
2609-5096	700W	730 mm	703 mm	185 mm	£692.95	£682.95
2609-5099	1 kW	730 mm	865 mm	185 mm	£762.95	£752.95
2609-5102	1.25 kW	730 mm	1069 mm	185 mm	£833.95	£823.95
2609-5105	1.5 kW	730 mm	1069 mm	185 mm	£913.95	£903.95







Pushbutton Timer and Thermostat

- Compatible with Heatstore wireless heaters including ceiling heaters
- Basic mode: Power On / Off with single press
- Four stage run back timer: 5, 15 or 30 mins [which can be increased to 20, 60 or 120 mins with four presses]
- Comfort temperature control
- Can be used for frost protection
- Mounted: Surface





Code	1+	3+
2379-6442	£34.50	£33.50

Run Back Timer and Variable Thermostat

- Compatible with Heatstore wireless heaters including ceiling heaters
- Current room temperature displayed, or target temperature once pressed
- Four stage run back timer: 5, 15 or 30 mins
- Comfort temperature control
- Can be used for frost protection
- Mounted: Surface





Code	1+	3+
2379-6460	£62.50	£61.50



Hand Dryers

Levanté

900W Tempesta Stainless Steel Hand Dryer

- Selectable power rating at installation: 600 / 900W
- Sensing distance: 100 mm
- Drying time: 10 secs
- Dimensions:300 mm[H] x 250 mm[W]x 159 mm[D]
- IP22

2183-7592



£	+VAT
1+	2+
£144.95	£141.95

2 YEARS Guarantee

kgC02e SAVING
UP 201-48
T0 kgC02e

105 m/s

UP **£241.97** OVER 365 DAYS

Decibel Rating

80 dB[A] @ 1 m

ENERGY SAVING COMPARISON: Traditional 1.8 kW Hand Dryer [Dry time 30 secs] vs Tempesta 600W [Dry time 10 secs]. Based on a medium footfall of 200 people per day.

800W Tempesta Plus Stainless Steel Energy Efficient Hand Dryer

- Auto-selects power rating depending on ambient temperature
- Sensing distance: 100 mm
- Drying time: 10 secs
- Dimensions: 278 mm[H]x 228 mm[W] x 154 mm[D]
- IP22





Code	Air Speed	Decibel Rating	1+	2+
2183-7595	85 m/s	70 dB[A] @ 1 m	£199.95	£196.95

kgC02e SAVING
UP 218-27
TO 218-27
kgC02e

VOU SAVE
UP **£262.**13 OVER 365 DAYS

ENERGY SAVING COMPARISON: Traditional 1.8 kW Hand Dryer [Dry time 30 secs] vs Tempesta Plus 200W [Dry time 10 secs]. Based on a medium footfall of 200 people per day.

Heat Recovery & Ventilation

Whisper Continuous All-In-One Fan

- Type: Axial with mixed flow impeller
- Speeds: 5 [intermittent and continuous options]
- Power rating: 0.7 3.4W
- Airflow: 22 83 m³/h
- Decibel rating: 10 21 dB[A] @ 3 m
- Built-in backdraught shutter
- Mounted: Wall or ceiling
- IP45



Code	Operation	1+	3+
Mains Voltage	[230V]		
2624-3890	Timer [2 - 30 mins] + Humidistat [60 - 90%]	£135.95	£133.95

Zone 1 Whisper Quiet Fan

- Type: Axial
- Uses Whisper Air Movement Efficiency to achieve near-silent running
- Power rating: 7.5W
- Airflow: 97 m³ / h
- Decibel rating: 25 dB[A] @ 3 m
- Built-in backdraught shutter
- Mounted: Wall or ceiling
- IP45



1DDVENT

Code	Operation	1+	3+
Mains Voltage	[230V]		
2561-2759	Timer [2 - 30 mins]	£51.95	£50.25

Single Room Heat Recovery Unit

- Up to 93% heat recovery
- Acoustic external wall vent reduces noise and draughts
- Power rating: 1.5W / 2.5W / 4.5W
- Airflow: 15 / 30 / 50 m³ / h
- Decibel rating: Up to 20 dB[A] @ 3 m
- IP2X

Code	1+	3+
Mains Voltage [230V]		
2733-1471	£358.50	£352.50









63A Econo-Mizer Single Phase Single Tap Voltage Optimisation Unit

- Suitable for home use and small business premises including:
 Hotels, restaurants, pubs, offices and retail units
- Reduces electricity consumption by up to 14%
- Prolongs the life of your electrical appliances by carefully reducing the voltage to 220V
- Works with solar PV, wind power and heat pumps
- Knockout: M32
- IP31



5 YEARS GUARANTEE

Includes:

- 100A 2 Pole isolator
- 63A C Curve single pole MCB

Code	Height	Width	Depth	1+
2 Pole – Sin	gle Tap 7.5%			
2171-3353	230 mm	310 mm	100 mm	£401.95

YOU SAVE

REDUCES ELECTRICAL EQUIPMENT'S ENERGY CONSUMPTION AND CARBON FOOTPRINT UP TO 14%

ONLY £401.95





100A Econo-Mizer Single Phase Multi Tap Voltage Optimisation Unit

- Suitable for use in homes and smaller business premises
- Reduces electricity consumption by up to 19%
- Three fixed tap settings: 6, 8 & 10% for optimum voltage control
- Supplied complete with full circuit protection
- Saves you money 24 hours a day, 7 days a week
- Silent operation
- Reduces carbon footprint

- Prolongs the life of your electrical appliances
- Works with solar PV, wind power and heat pumps
- Easily installed by a qualified electrician
- Immediate savings
- No maintenance





1830-3052 250 mm 140 mm **CONTACT YOUR NEAREST BRANCH FOR FURTHER DETAILS** 380 mm

YOU SAVE

REDUCES ELECTRICAL EQUIPMENT'S ENERGY CONSUMPTION AND CARBON FOOTPRINT UP TO 19%











Enclosed Variable Speed Drives

- Range: Easy Speedy
- Enclosed inverter panel supplied ready to run with the latest Emotron FDU and VS inverters fitted as standard
- Integral EMC filter and keypad / display
- Simple Start / Stop buttons
- Internally-mounted, adjustable energy-saving potentiometer
- Removable gland plates
- IP54
- BS EN 60947





Code	Current Rating	kW Rating	Height	Width	Depth	1+
Single Phase – 230V						
2179-6921	1.7A	0.25 kW	300 mm	300 mm	200 mm	£743.95
2179-6924	2.4A	0.37 kW	300 mm	300 mm	200 mm	£751.95
2179-6927	3.2A	0.55 kW	300 mm	300 mm	200 mm	£810.95
2179-6930	4.2A	0.75 kW	300 mm	300 mm	200 mm	£834.95
2179-6933	6A	1.1 kW	400 mm	300 mm	200 mm	£910.95
2179-6936	7A	1.5 kW	400 mm	300 mm	200 mm	£911.50
2179-6939	9.6A	2.2 kW	400 mm	300 mm	200 mm	£1,009.95
3 Phase – 400\						
2179-6942	1.3A	0.37 kW	300 mm	300 mm	200 mm	£857.95
2179-6945	1.8A	0.55 kW	300 mm	300 mm	200 mm	£869.95
2179-6948	2.4A	0.75 kW	300 mm	300 mm	200 mm	£891.95
2179-6951	3.2A	1.1 kW	400 mm	300 mm	200 mm	£1,010.95
2179-6954	3.9A	1.5 kW	400 mm	300 mm	200 mm	£1,034.95
2179-6957	5.6A	2.2 kW	400 mm	300 mm	200 mm	£1,069.95
2179-6960	7.3A	3 kW	400 mm	300 mm	200 mm	£1,199.95
2179-6963	9.5A	4 kW	400 mm	300 mm	200 mm	£1,384.95
2179-6966	13A	5.5 kW	400 mm	300 mm	200 mm	£1,464.95
2179-6972	16.5A	7.5 kW	500 mm	400 mm	200 mm	£1,692.50

10% SLOWER = UP TO 25% SAVING 20% SLOWER = UP TO 45% SAVING 30% SLOWER = UP TO 65% SAVING

YOU SAVE

2 YEARS GUARANTEE

FROM £743.95

We're all about renewables

Sustainable solutions made easy

As well as **Solar Panels**, we stock hundreds of renewable products to meet your needs including:

Mounting



Batteries & Inverters



EV Charging



Air Source Heat Pumps



 $\langle \rangle$

Extensive product range

Wide range of **industry-leading** products, available when you need them



Expert support

Local renewables **experts nationwide** to help with specifications and technical queries



What you need, at speed

On-time delivery to keep your projects on track



Where you need it

Nationwide stock availability through **over 390 branches**





Multifunction Installation Tester with EV Testing Adaptor - Ethos 8560 EV Test Kit

■ Simple to operate – just select and test









Shopping made simple

We make it easy to get the tools and supplies you need, however and whenever you prefer to shop





cef.co.uk

Browse, compare, and get the details you need to make the right choice, all with next-day delivery*

*Geographical restrictions may apply



Trade App

Discover speed and convenience at your fingertips



In Branch

Find trusted brands, expert advice and thousands of products all in one place




cef.co.uk











Did you know CEF can now offer simple fixed-term lease finance for many of your product needs?

A wide range of equipment can be financed, including energy saving products such as lighting.

Products available with finance options include:

- CCTV
- Alarm systems
- Heating products
- Lighting [including LED Lamps]
- Inverters
- Solar PV
- Test equipment
- Air conditioning
- Hand dryers
- Air purifiers
- Domestic appliances [for commercial use]

Plus many more products









DON'T FORGET We also offer free of charge surveys and design schemes

£500 is the minimum amount which can be financed. Terms and conditions as per the finance Company and are subject to formal credit approval and underwriting. Private sector Companies must have Limited or PLC status. E & O E





Financing equipment through your local CEF store makes good business sense

Some of the key benefits to your organisation include:

- Convenient and fast
- Makes the right solution for your business affordable – right now!
- Conserves working capital and existing credit lines

- Tax efficient
- Fixed payments and flexible terms
- Quick and straightforward application process

CEF will help you identify the right products for your business and our Finance Department will guide you through the easy steps of accessing finance:











FOR FURTHER INFORMATION PLEASE CONTACT YOUR LOCAL STORE

Sustainable Electrical Waste Recycling



Protecting our future, together

CEF are the **only electrical distributor** in the UK with an in-house electrical waste recycling facility, offering a complete one-stop recycling service and ensuring compliance with all current legislation.

Did you know?

- We recycle over 1 million lamps each year.
- We recycle more electrical waste than any other UK distributor.
- 98% of the electrical waste we receive is recycled.
- Our nationwide network of over 390 branches provides convenient service.



Visit wasteexperts.co.uk for more information





Contact your local branch for more details

